

## TECHNICAL DATA

### MACHINE PROTECTION CLASS I



Voltage	V~	230
Frequency	Hz	50/50
Power	W	3400, 4000
Temperature °C	20-620	progressive
Drive m/min	1-18	
Noise emissions level	<70dB	
Weight kg	17,5	(with connection cable)
Mass mm	535 x 280 x 350 mm	(without guide handle)

## Device description

### FORPLAST-P2

1. Housing
2. Mains connection cable
3. Carrying handle
4. Lifting facility for neutral gear
5. Guide roller of lifting facility
6. Permanent feed switch
7. Drive roll
8. Blank holders
9. Deflection roller
10. Startup switch
11. Welding nozzle
12. Guide arm with guide roller
13. Speed knob
14. Telescopic guide pole
15. Hot air fan
16. Main switch
17. Green indicator lamp (ready-to-use)
18. Red indicator lamp (error report)
19. Temperature knob
20. Heat stage switch
21. Hot air fan main switch

## COMMISSIONING

### FORSTHOFF FORPLAST-P2

#### Ready-to-use



- Before commissioning, check the mains connection cable (2) and plug for electrical and mechanical damages.
- Pull out the hot air fan (15) on the guide carriage with the star handle and tilted upwards as far as it will go
- Mount the telescopic guide pole and adjust it to the required height. The handle can be extended from 835 mm to 1085 mm.
- Connect the device to the mains. The mains voltages must match the device voltage. The indicator lamp (17) flashes green.
- Switch the device on with the main switch (16). The indicator lamp (17) flashes green to show that the device is ready for use. Also switch the hot air fan (15) on at the main switch (20).
- Set the potentiometer for the air temperature (19) to the required value.
- Set the potentiometer for the speed (13) to the required value.

- After the end of welding work, set the potentiometer for the air temperature to zero so that the hot air fan can cool down or switch the heat stage switch (20) of.
- Switch off the hot air fan on the main switch (21) to the 0 switch position.
- Switch off the welding machine on the main switch (16) to the 0 switch position and disconnect the device from the mains.

#### FORPLAST-P2 accessories

- Only FORSTHOFF accessories may be used
- Additional weight

#### Maintenance and repairs

- Clean the air outlet openings on the machine and air filter of the hot air fan with a brush if there is any soiling.
- When the minimum length of the carbon brushes is reached, the fan motor automatically switches off. The carbon service life is a minimum of 1500 hours. Only allow carbon brushes to be replaced by an authorised service point or specialist company.
- Clean welding nozzles (11) with a wire brush
- Check the mains connection cable (2) and plug for electrical and mechanical damages.
- Only allow repairs to the device to be performed by an authorised repair workshop.

#### Welding process

- Position the welding machine over the planned welding seam with the lifting facility (4). Using the switch for permanent feed (6), the device can be positioned with motor power in the direction of welding without pivoting the hot air fan.
- Pivot the hot air fan as far as possible into the welding seam using the star handle. The machine is automatically started using startup automation. During the welding process, the indicator lamp (17) permanently illuminates green.
- After welding, the hot air fan is withdrawn from the welding seam with the star handle and pivoted up as far as possible. The machine feed stops automatically.



### Disposal

Do not dispose of the device in the household waste! Always recycle the device with separate collection of materials to protect the environment.

### Assistance in case of problems

# Barnes

Plastic Welding Equipment Ltd.

Barnes Plastic Welding Equipment Ltd,  
Unit, 11, Hamilton Street, Blackburn, BB2 4AJ.  
Tel: 01254 660910

### EC Declaration of Conformity

conforms to the regulations of the following European directives:  
EC directive 2006/95/EC - LVD  
EC directive 2004/108/EC – EMC

The specified product's conformity with the regulations of directive 2006/95/EC is proven by compliance with the following norms:  
EN 60335-1:2002 + A11:2004 + A1:2004 + A12:2006 + Corrigendum: 2006 + A2:2006  
EN 60335-2-45:2002

Last two figures of the year in which the CE mark was applied: 10

The specified product's conformity with the regulations of directive 2004/108/EC is proven by compliance with the following norms:  
EN 55014-1:12/2006  
EN 55014-2:02/1997+A1:12/2001  
EN61000-3-2:4/2006  
EN61000-3-3:1/1995+A1:6/2001+A2:11/2005

This declaration certifies compliance with the specified directives, but does not provide assurance of the properties in the legal sense. The safety information supplied with the product documentation must be observed.

Solingen, 01.09.2010

Andrea Forsthoff-Neeff  
General Manageress, Company Owner

### Warranty

A one-year warranty is provided for this device from the date of purchase (proof provided with an invoice or delivery note). Any damages will be addressed with a replacement delivery of repair. Heating elements are excluded from this guarantee.

Subject to the provision of legal regulations, all other claims are excluded.

Damages caused by natural wearing tear, overload or inappropriate use are excluded from the warranty.

No claims can be made for devices that have been converted or changed by the purchaser.

Technical changes are reserved.

